

DURA-FLAT MATTING AGENT FOR HIGH GLOSS SEALER

DESCRIPTION: Proline's DURA-FLAT is an easy to use matting agent additive for Proline's solvent-based sealers when a Satin/Matte finish is desired.

USES: Add to Proline's solvent sealer to bring down the shine to a Satin/Matte sheen. Ideal applications for stamped concrete, broom finish, acid stained concrete, patios, driveways/sidewalks and many more interior and exterior concrete where a low shine, satin finish is preferred.

ADVANTAGES

- Excellent suspension characteristics
- Reduce inventory & save storage space oppose to offering 2 separate sealers.
- Never run out of stock of matte sealer as long as you stock DURA-FLAT
- Easily transforms a high gloss sealer to a matte finish
- Contains 0 g/L VOC content.

PREPARATION: Surface must be dry, porous and free of foreign contaminants. Remove efflorescence, oil, dirt, wax, old paints, sealers, and curing compounds. Rinse thoroughly. Allow surface to fully dry. Substrate and air temperature must be between 40°F to 85°F.

APPLICATION: Combine the desired amount to Proline's high gloss sealer. Mechanically mix with a jiffy type mixer for a minimum of 2 minutes, making sure the DURA-FLAT additive is mixed thoroughly. It is very important to mix thoroughly to ensure best result. Not mixing correctly may result in an uneven finish where there are high shine areas and matte areas.

SUGGESTED AMOUNTS**

5 Gallon of High Gloss Sealer

Satin Finish - add 1 pint (entire jar = 25 grams)

Matte Finish - add 2 pints (2 jars)

1 Gallon of High Gloss Sealer

Satin Finish - add 5 grams (by weight)

Matte Finish - add 10 grams (by weight)

**FOR BEST RESULTS: TEST PRIOR TO APPLICATION FOR DESIRED GLOSS REDUCTION

CLEAN UP: Follow cleaning instructions for the sealer used. DURA-FLAT additive does not require special cleaning instructions.

SHELF LIFE AND STORAGE: Must be kept dry and moisture free, out of direct sunlight. DURA-FLAT will absorb moisture and will no longer be effective. If kept in the correct conditions, shelf life should be a minimum of 12 months from the date of purchase.

CAUTION: KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. **DO NOT TAKE INTERNALLY.** Do not breathe vapors or mist. Use only with adequate ventilation and use a respirator when levels are above applicable limits. If using spray equipment, a painter's mask should be worn. Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product and wash and bathe after each use. Be sure to wash clothing after each use

WARRANTY: This product is not for public use and is intended for use by licensed contractors, experienced and trained in the use of these products. It is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.