



DURA-REVEAL™ SURFACE DEACTIVATOR

DESCRIPTION AND BASIC USE: Proline DURA-REVEAL™ is a sprayable surface deactivator designed to create a variable etch exposed finish by preventing the hydration of the cement on the surface of concrete.

BENEFITS:

- * Depth Control
- * No need to cover with poly
- * Consistent Finish
- * Deactivates surface permanently
- * Cures per ASTM C-309

COVERAGE: One gallon covers approximately 200 - 300 square feet on most surfaces or until surface is completely covered.

TOOLS AND MATERIALS REQUIRED: 1) Low Pressure Sprayer 2) Pressure Washer 3) Eye protection, rubber gloves & paper mask.

CONCRETE MIX DESIGN: DURA-REVEAL™ is designed for standard 6 sack mix. A sample should be made under similar site conditions and mix to ensure desired results.

APPLICATION: **MIX WELL BEFORE AND DURING USE.** Apply immediately after bleed water has evaporated. DURA-REVEAL™ should be applied with a low pressure sprayer evenly over the surface. Care should be taken to ensure even coverage rate. There is no need to cover with poly sheeting as DURA-REVEAL™ forms a film that is resistant to wind and rain.

DWELL TIME: Environmental conditions and mix design may affect the performance of DURA-REVEAL™. Under normal conditions with a standard mix design, the surface can be exposed after 14+ hours. There is no limit to how long DURA-REVEAL™ can dwell. If left on fresh concrete for 28 days, DURA-REVEAL™ meets ASTM C-309 type II as a curing compound.

NOTES: This product is not intended for full, exposed aggregate and it is also not intended for vertical application.

TECHNICAL DATA:

VOC: < 100 G/L
Flash Point: N/A

HMS: Health = 1, Flammability = 0, Reactivity = 1, Protection = B

CAUTION: KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. **DO NOT TAKE INTERNALLY.** Avoid contact with skin and eyes. Use only with adequate ventilation and use a respirator when exposure levels are above applicable limits.

WARRANTY: This product is not for public use and is intended for use by licensed contractors, experienced and trained in the use of these products. It is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.